



DGN FASER PRIVATE LIMITED

R.S. No. 565, Surendranagar – Lakhtar Highway, Near Dedadra Patiya, Surendranagar – 363030 (Guj.)

Phone : 02752-283383. E mail: dgnfaser@gmail.com

Accredited with QMS 9001-2015, EMS 14001-2015 & OH & SAS 18001-2015

Technical Data Sheet

1. Product	:	Ceramic Fibre Blanket, Grade: 1260°C
2. Size	:	7.300 mm X 0.610 mm X 25 mm Thickness,
3. Density	:	160 Kg/m ³ (-10%, + 30%)
4. Dimensional	:	
Length (mtr.)	:	7.3 (-0, excess is permitted)
Width (mtr.)	:	0.610 (-2%, +10%)
Thick (mm)	:	25 (-2mm, +3mm)
5. Shot Content	:	30% max.
6. Tensile Strength	:	50 kPa
7. Linear Shrinkage	:	3.5 % max
(at 1260°C for 24 Hours)		
8. Fibre Diameter	:	2.0 to 4.0 micron
9. Thermal Conductivity	:	0.145 W/mk
(at Mean Temperature 500°C)		
10. Chemical Composition	:	
Al ₂ O ₃ %	:	42 – 47
SiO ₂ %	:	51 – 57
ZrO ₂ %	:	0 – 7
Fe ₂ O ₃ %	:	0.1 Max
Leachable	:	0.3% Max

Material will be as per ASTM C 892 / IS: 15402 Specification